

OMV BIXXOL extra SAE 10W-40

Product no.: 163030

The Product:

OMV BIXXOL extra is a semi-synthetic multigrade engine oil for **today's gasoline and diesel engines**, even with turbocharging or catalytic converters. It permits severe operating and traffic conditions and thereby guarantees full reliability.

Distinctive features of OMV BIXXOL extra – and why You should use it

Winter viscosity reduces friction during cold operation

Easy, battery saving cold start

Stable summer viscosity

Reaches every part of the engine, highest security during urban stop-and-go-traffic

Qualified for turbo-charged engines and catalytic converters

High reserves in performance within the recommended oil drain interval

Low volatility

Reduces oil consumption

Specifications:

ACEA A3/B4, API SM/CF

Approvals:

MB 229.3, VW 502 00/505 00

Subject to change without notice. Please consult the original equipment manufacturers' manuals.

Further information can be requested from PM Lubricants +43-1-40440-27281 or info.lubricants@omv.com

Technical Data (typical values)

Property	Unit	OMV BIXXOL extra
Density/15°C	Kg/m ³	868
Flash point COC	°C	226
Viscosity class	SAE	10W-40
Viscosity/40°C	mm ² /s	110,0
Viscosity/100°C	mm ² /s	14,8
Viscosity index	---	158
CCS/-20°C	mPa.s	6262
Pour point	°C	<-33

A material safety data sheet can be downloaded from www.omv-bixxol.com or www.omv.com.

Subject to change without notice. Please consult the original equipment manufacturers' manuals.

Further information can be requested from PM Lubricants +43-1-40440-27281 or info.lubricants@omv.com