

Product Data Sheet



OMV BIXXOL premium SAE 5W-40

Product no.: 163000

The Product:

OMV BIXXOL premium is a synthetic fuel economy engine oil for **gasoline and diesel engines of the newest generation**. It offers best lubrication and thus highest reserves of operational safety and performance.

Distinctive features of OMV BIXXOL premium - and why You should use it

Allows most severe operational conditions

Extremely high engine operating

reliability

Reduces friction of moving parts

Highest economic efficiency – reduces

fuel consumption

Excellent low temperature properties Allows quick start-up at low

temperatures in winter

Optimum lubrication due to Maximum reliability during stop-and-

"stay-in-grade"-viscosity go-traffic

Excellent wear protection Increases engine life

Long oil drain intervals High economy

Lowest volatility Reduces oil consumption

Specifications:

ACEA A3/B4, API SM/CF

Approvals:

GM-LL-B-025, VW 502 00/505 00, MB 229.3



Product Data Sheet



Technical Data (typical values)

Property	Unit	OMV BIXXOL premium
Density/15°C	Kg/m³	855
Flash point COC	°C	228
Viscosity class	SAE	5W-40
Viscosity/40°C	mm²/s	87,30
Viscosity/100°C	mm²/s	14,50
Viscosity index		167
CCS/-30°C	mPa.s	5850
Pour point	°C	<-36

A material safety data sheet can be downloaded from www.omv.com or www.omv.com.