

Product description

OMV full syn plus SAE 5W-30

Product number: 168870
OMV Deutschland: 8052

OMV full syn plus SAE 5W-30 is a new developed fully-synthetic motoroil with evident fuel-economy properties.

Properties

- Guarantees maximum fuel-economy due to reduced high-temperature-viscosity
- Latest additive-technology reduces inner friction and ensures high efficiency
- Enables long maintenance intervals according to BMW Longlife-01 and MB 229.5
- Excellent lubrication properties reduce wear during warm up
- Excellent wear protection guarantees long engine life-cycle
- Keeps the engine clean and prevents from deposits
- Can be mixed with all brand oils, although its full performance is only achieved unmixed

Applications

OMV full syn plus SAE 5W-30 was developed for use in modern high-performance engines including all turbo-charged engines. OMV full syn plus SAE 5W-30 provides a maximum in performance and engine-protection and is perfectly suitable for extended ODI.

Specifications

Exceeds ACEA A3/B3/B4, API SL/CF

Approvals

BMW LL-01, MB 229.5, VW 502 00/505 00

Technical data (typical values)

Property	Unit	OMV full syn plus SAE 5W-30
Density/15°C	Kg/m ³	858
Flash point COC	°C	235
Viscosity class	SAE	5W-30
Viscosity/40°C	mm ² /s	68
Viscosity/100°C	mm ² /s	12.2
Viscosity index	---	178
CCS/-35°C	mPa.s	5750
Pour point	°C	<-36

A viscosity/temperature diagram and a safety data sheet are available on request.