

# Product description

## OMV super start SAE 15W-40

Product code: 168100

OMV super start SAE 15W-40 is a mineral based multigrade engine oil for passenger cars and light duty trucks. It is blended from high quality solvent neutrals and a carefully balanced high performance additive package.

### Properties

- Universal in use due to its wide performance profile
- Excellent viscosity-temperature behaviour
- Excellent cold start properties in winter and stable lubricating film in summer
- Excellent detergency to remove deposits
- Keeps the engine clean and protects from sludge
- High aging stability
- Protects from rust and corrosion
- Compatible with all commonly used elastomers

### Application

OMV super start SAE 15W-40 can be used for modern gasoline and diesel engines in passenger cars and light duty trucks with or without turbo- or supercharger. It is suitable for all seasons and for all operational conditions and provides reliable engine protection.

### Specifications

API SJ/CF, ACEA A3/B3/B4, VW 501 01/505 00

### Technical Data (typical Values)

Property	Unit	OMV super start SAE 15W-40
Density/15°C	Kg/m <sup>3</sup>	883
Flash Point COC	°C	226
Viscosity class	SAE	15W-40
Viscosity/40°C	mm <sup>2</sup> /s	110
Viscosity/100°C	mm <sup>2</sup> /s	14.9
Viscosity index	---	> 135
CCS/-20°C	mPa.s	<7000
Pour Point	°C	< -27

A Material Safety Data Sheet is available under [www.omv.com](http://www.omv.com) and can also be provided on request.