

Product description

OMV super start SAE 20W-50

Product code: 168101

OMV super start SAE 20W-50 is a mineral based multigrade engine oil for passenger cars and light duty trucks. It is blended from high quality solvent neutrals and a carefully balanced high performance additive package.

Properties

- Universal in use due to its wide performance profile
- Excellent viscosity-temperature behaviour
- Excellent cold startig properties in winter and stabel lubricating film in summer
- Excellend detergency to remove deposits
- Keeps the engine clean and protects from sludge
- High aging stability
- Protects from rust and corrosion
- Compatible with all commonly used elastomers

Application

OMV super start SAE 20W-50 can be used for modern gasoline and diesel engines in passenger cars and light duty trucks with or without turbo- or supercharger. It is suitable for all seasons and for all operational conditions and provides reliable engine protection.

Specifications

API SJ/CF, ACEA A3/B3/B4, VW 501 01/505 00

Technical Data (typical Values)

Property	Unit	OMV super start SAE 20W-50
Density/15°C	Kg/m ³	888
Flash Point COC	°C	230
Viscosity class	SAE	20W-50
Viscosity/40°C	mm ² /s	156
Viscosity/100°C	mm ² /s	18.5
Viscosity index	---	> 135
CCS/-15°C	mPa.s	<7000
Pour Point	°C	< -27

A Material Safety Data Sheet is available under www.omv.com and can also be provided on request.